

E-IVIX PATENT PENDING ELECTRIC VARIABLE RATIO SPRAYER







ELECTRIC POWERED ELIMINATE THE COMPRESSOR AND SAVE \$\$

XT BREAKTHROUGH PERFORMANCE

- Variable Ratio from 1:1 to 6:1
- Flow rates up to 3.8 lpm (1.5 gpm)
- 5000 psi Max Pressure
- Tip support to .039

XTREME TORQUE™ MOTORS

- Low RPM, high torque design offers long life and unmatched performance
- Silent operation for comfort and extending spray times in restricted areas
- · Made in the USA by Graco

DUAL ENDURANCE® PUMPS WITH PROCONNECT®

- Job site proven Chromex Rod and Chrome cylinder for exceptional life and durability
- Balanced double-displacement design for ratio accuracy
- Quick & easy pump removal with just a hammer - perfect for on-the-job maintenance

DUALFLO™ ON-DEMAND FLUID HEATER

- Offers independent heat for A & B components
- 4000 watt power provides up to 15°C (60°F) delta T heat rise for easier spraying
- · Adjusts right from the touch screen

EASY TO MANOEUVRE DESIGN

 Heavyduty painted steel construction with integrated lift points and flat proof tires



WHAT CONTRACTORS ARE SAYING...

"On our very first job, we saw at least a **15% savings** on materials (coatings and solvent) compared to hot potting...In fact, we plan on phasing out our Kings and moving the rest of the crews to E-Mix XT"

- Manuel Rodriguez, Co-owner, Polytech Industrial Inc., Fresno, CA



THE EASIEST TO OPERATE VARIABLE-RATIO SPRAYER IN THE INDUSTRY



SO EASY, YOU CAN RUN IT FROM A SINGLE TOUCHSCREEN

SMARTSYNC™ CONTROL WITH TOUCH-SCREEN INTERFACE

• All important spray parameters are controlled from one screen — nothing could be easier

• Eliminates the steep learning curve — no expert needed

• Perfectly syncs the XT motors and pumps to deliver the perfect ratio — *everytime*

FEATURING RATIOGUARD PROTECTION

- Real-time ratio monitoring maintains accuracy
- Integrated alarm system prevents errors and eliminates rework

INTEGRATED RATIO CHECK

- Proves on-ratio accuracy for each mix ensuring quality
- Ideal for inspections and quality control checks
- Single-handle design for easy, efficient operation

FASTCLEAN™ SOLVENT PUMP

- Allows quick flushing of mix hose and gun during stoppage to protect your equipment
- Features 18.9 litres (5 gallon) inlet suction set for solvent bucket
- Powered by Xtreme Torque Motor and Endurance pump for long life and trouble-free operation



INCREASE PROFIT & QUALITY WITH **E-MIX XT!**





READY-TO-SPRAY SOLUTIONS FOR EVERY JOB

Choose from Standard Series for work where a remote manifold is not required, or choose the Pro Series for longer hose runs with a remote manifold — *you decide*



E-MIX XT STANDARD INCLUDES:

- E-Mix XT (400V, 3-Phase Power)
- Dual 26.5 Litre (7 Gallon) Hoppers
- FastClean Solvent Flush Pump
- DualFlo Heater
- Ratio Check Kit
- 7.6m x 9.5mm (25' x 3/8") Mix Integration Hose
- 3.0m x 6.4mm (10' x 1/4") Whip Hose
- XTR 5+ Gun, XHD 519 Switch Tip



E-MIX XT PRO INCLUDES:

All the STANDARD Features

PLUS:

- Light Tower
- Hose Rack
- Remote Manifold Carriage

4 x - 15.2m x 12.7mm (50'x 1/2") "A" & "B" Material Hoses

2 x - 15.2m x 9.5mm (50' x 3/8") "B" Material Hose (ratios over 3:1)

E-MIX XT 240v	PART #
E-Mix XT Standard Series	2004088
E-Mix XT Pro Series	2005567



Scan for more information

