


BINKS MX LITE SERIES

Air Assisted Airless and Airless Spray Packages

FLUID HANDLING



BINKS MX LITE SERIES Air Assisted Airless Piston Pumps

The Binks MX LITE spray packages include the Binks Stainless Steel MXL high pressure pumps with Binks Trophy AA Air Assisted Airless or A75 Airless Spray Guns.

MX LITE outfits have been designed to provide users with a low cost, robust industrial spray outfit, able to apply a wide range of industrial coatings whilst providing the very best quality of spray finish.



COATING TYPES AND APPLICATIONS

AFROSPACE

Suitable For These Materials:

- Wood-Stains, Lacquers & Varnishes
- Primers, Sealers & Catalysed Lacquers
- Solvent OR Waterborne Coatings
- Enamels & Polyurethane's
- Plus many others...



WOOD

AGRICULTURAL AND OFF ROAD MARINE INDUSTRY TRUCK

TRUCK AND BUS

BINKS MX LITE SERIES FEATURES

Patented Air Valve Technology: Enables pump to change over quickly to significantly reduce pulsation

Long Lasting Ceramic Coated Piston Rods: Superior wear resistance lasting up to three times longer than hard chrome pistons

Designed To Pump Longer With Less Downtime & Extended Packing Life: Self-adjusting spring loaded fixed packings last up to 3X longer than the competition. Large sight glass for visual packing inspection

Binks Trophy AA and A75 guns: Provide the latest atomisation technology

Stainless Steel system—pump and gun

5 Year Limited Warranty: Best in class warranty for finishing equipment. Manufactured to ISO9001







Quality Passport for Binks MX LITE Pumps:

- Modular construction means reduced number of parts for easy and fast maintenance.
- All wetted parts are Stainless Steel—Ideal for use with solvent and water based paints/materials
- Fixed, spring tension packings—Lower maintenance and reduced running costs
- All valve seats are Tungsten Carbide Long durable working life
- Ceramic coated piston—Extra wear resistance, longer packing life.
- Pump packings PTFE/UHMWPE mix (other packing choices available).

MX LITE Packages include:-

Binks MXL pump mounted on tripod/wall/cart/pail with gun, air and pump fluid controls. 7.5 metre Air and Fluid Hoses. Binks Trophy AA 4400 with AA10 air cap* or A75 Spray Gun and Tip with gun mounted stainless steel edge type fluid filter. (*Tip size to be specified at time of order)

Binks Trophy AA spray gun The best "fit and feel" of any AAA gun around

- Light weight gun with ergonomic handle reduces operator stress and fatigue
- Light trigger-pull design for less operator strain & RSI
- Easy to remove "IN-LINE" needle reduces repair time
- One tool trigger removal speeds up maintenance and downtime
- · Adjustable packing can be tightened without disassembly
- Anodized aluminium air caps guard against corrosion
- HVLP and LVMP Technologies provide a wider choice of spray options
- Unique Twist Tip option quickly & easily removes clogs

Trophy AA	A75
1/4" BSP/NPS (M)	1/4" NPS
Stainless Steel	Stainless Steel
540g	660g
Forged Aluminium	Anodised Aluminium
303 bar (4400 psi)	571 bar (7500 psi)
6.9 bar (100 psi)	=
Tungsten Carbide	=
100 mesh	-
	1/4" BSP/NPS (M) Stainless Steel 540g Forged Aluminium 303 bar (4400 psi) 6.9 bar (100 psi) Tungsten Carbide

Air Assisted Airless Piston Pumps

PUMP SPECIFICATIONS					
Pump Specification	MXL 4/12	MXL 4/32	MXL 12/05	MXL 12/12	MXL 12/31
Ratio	12:1	32:1	4.8:1	12:1	31:1
Max inlet pressure	8.0 bar (116 psi)	8.0 bar (116 psi)	8.0 bar (116 psi)	8.0 bar (116 psi)	8.0 bar (116 psi)
Flow rate nominal	1.4 l/min	1.4 l/min	4.3 l/min	4.3 l/min	4.3 l/min
Flow rate max	4.0 l/min	4.0 l/min	12 l/min	12 l/min	12 l/min
Volume/Cycle	24 cm ³	24 cm ³	72 cm ³	72 cm ³	72 cm ³
Max operating pressure	96 bar (1390 psi)	256 bar (3600 psi)	39 bar (557 psi)	96 bar (1390 psi)	248 bar (557 psi)
Cylinder Diameter	55 mm	85 mm	55 mm	85 mm	140 mm
Piston Stroke	75 mm	75 mm	75 mm	75 mm	75 mm
Air consumption @ 20 cycles/min	62.5 l/min	147 l/min	62.5 l/min	147 l/min	498 I/min



Premium fine finish and twist tip range available



Optional dump valve adaption kit for outfits without filters. Pt No. 0115-010672

MX Lite Ordering Information	B - PACKINGS	D - OPTIONS
MXL A B - C - D - E Bare Pump	PU = PTFE/UHMWPE Supplied as standard PL = PTFE/Leather PP = PTFE/PTFE Excl. 1205	= No Filter Leave blank F = Filter 100 Mesh G = Gravity Hopper 432(W or C or T) Only
A - PUMP TYPE 1205 = 12 I/min - Ratio 5:1	UC = U-Cups C - MOUNTING TYPE	FG = Filter & Hopper 432(W or C or T) Only E - TECHNOLOGY
1212 = 12 /min - Ratio 3.1 1212 = 12 /min - Ratio 12:1 1231 = 12 /min - Ratio 31:1 1231 = 4 /min - Ratio 12:1 432 = 4 /min - Ratio 32:1	W = Wall C = Cart T = Tripod 412 & 432 Only P = Pail 432 only	AC = Air Assisted Airless Controls ACG = AAA with Trophy AA Spray Gun + 7.5m Hoses AL = Airless Controls 1231PU / 432PU Only ALG = Airless with A75 Spray Gun + 7.5m Hoses 1231PU / 432PU Only

Choose the Binks MXL Pump Outfit for your application from the chart below:

Binks MX Lite Pump outfit Contents and Part Numbers	MXL412PU-T-AC	MXL412PU-W-AC	MXL412PU-T-F-ACG	MXL412PU-T-FG-ACG	MXL432PU-T-AC	MXL432PU-T-ACG	MXL432PU-T-F-ACG	MXL432PU-T-G-ACG	MXL432PU-T-FG-ACG	MXL432PU-W-AC	MXL432PU-W-F-AC	MXL432PU-W-F-ACG	MXL432PU-W-FG-ACG	MXL432PU-C-F-ACG	MXL432PU-C-FG-ACG	MXL432PU-P-F-AC	MXL1205UCU-W-F-AC	MXL1205UCU-C-F-ACG	MXL1212PU-W-F-AC	MXL1212PU-C-ACG	MXL1231PU-W-F-AC	MXL1231PU-W-ACG	MXL1231PU-W-F-ACG	MXL1231PU-C-AC	MXL1231PU-C-F-AC	MXL1231PU-C-F-ACG	MXL1231PU-W-F-AL	MXL1231PU-W-ALG	MXL1231-W-F-ALG
MXL 4/12 Bare Pump	_																												
MXL 4/32 Bare Pump					Q	Q	9			П	9	П				П													
MXL 12/05 Bare Pump																	ш	ш											
MXL 12/12 Bare Pump																													
MXL 12/31 Bare Pump																						П							
High pressure filter assy St St														П															
Pail Mounted																П													
Tripod Mounted				П	П	О	П																						
Cart Mounted														П	П			П		П				П	О	П			- 1
Wall Mounted																													
Airless controls																											П	П	
Air Assisted Airless controls																													
St St metal suction pipe/filter					П	П										П													
Flexible suction hose assy & filter										П	П																		
Gravity Hopper (6 litre)									П				П		П														
Hose & Gun			П			П	П	П	П			П	П	П	П			П		П		П	П			П		П	

Binks MXL pump outfits are fully assembled, tested and ready to spray.

Binks MXL Series 5-Year Warranty

Binks® warrants to the original end-use purchaser that the Binks branded products "MXL" shall not fail under normal use and service due to a defect in material or workmanship within five (5) years from the date of shipment from Binks.

Does not include normal wear and tear parts.



For further technical information refer to the Binks MX Lite Service Bulletins



SOLUTIONS FOR YOUR WORLD

www.carlisleft.com